

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/6

Holdtite A649

Revision 0

Revision date 2017-09-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Holdtite A649
---------------------	---------------

1.3. Details of the supplier of the safety data sheet

Company	Bondchem
Address	Unit 10 Lawson Street Dock Road Industrial Estate North Shields Tyne and Wear NE29 6TF
Web	www.bondchem.com
Telephone	+44 (0)191 2586990
Fax	+44 (0)191 2596853

1.4. Emergency telephone number


Emergency telephone number	+44(0)191 2586990
Company	Bondchem (Head Office) 24 hours (Diverted out of office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	F; R11 Xi; R36 R66-67 Symbols: F: Highly flammable. Xi: Irritant.
Main hazards	Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	: EUH066; Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment.

Holdtite A649

Revision 0

Revision date 2017-09-12

2.2. Label elements

Precautionary Statement: Response	P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to hazardous waste collection point. Refer to section 13.1 for waste treatment methods.

2.3. Other hazards

Other hazards	This product does not contain any substances classified as PBT or vPvB.
----------------------	---

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Acetone	606-001-00-8	67-64-1	200-662-2		90 - 100%	F; R11 Xi; R36 R66 R67	
Copper naphthenate	029-003-00-5	1338-02-9	215-657-0		0 - 0.5%	R10 Xn; R22 N; R50/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Acetone	606-001-00-8	67-64-1	200-662-2		90 - 100%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
Copper naphthenate	029-003-00-5	1338-02-9	215-657-0		0 - 0.5%	Flam. Liq. 3: H226; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause dizziness and headache. Inhalation may cause nausea and vomiting.
-------------------	---

Holdtite A649

Revision 0

Revision date 2017-09-12

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Irritating to eyes.
Skin contact	May cause sensitisation by skin contact.
Ingestion	Ingestion may cause nausea and vomiting. There may be vomiting and diarrhoea. There may be loss of consciousness. Convulsions may occur.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Use as appropriate: Carbon dioxide (CO ₂), Dry chemical, Foam.
--	--

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

Further information

	In case of fire evacuate area. Fire fight remotely due to the risk of explosion. Use water spray to cool unopened containers.
--	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Storage class (TRGS 510) Flammable liquids.
--	--

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Acetone	WEL 8-hr limit ppm: 500	WEL 8-hr limit mg/m ³ : 1210
	WEL 15 min limit ppm: 1500	WEL 15 min limit mg/m ³ : 3620
	WEL 8-hr limit mg/m ³ total -	WEL 15 min limit mg/m ³ total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m ³ total -	WEL 15 min limit mg/m ³ total -
	respirable dust:	respirable dust:


8.2. Exposure controls

Holdtite A649

Revision 0

Revision date 2017-09-12

8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Green
Odour	Strong
pH	No data available
Melting point	= -95 °C
Freezing Point	No data available
Initial boiling point	> 56 °C
Flash point	-18 °C
Flammability (solid, gas)	No data available
Vapour pressure	= 185
Relative density	= 0.79 (H ₂ O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	= -0.24 log P
Autoignition temperature	465 °C
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	Not applicable.
Solubility	No data available

9.2. Other information

Conductivity	No data available
Surface tension	No data available

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

10.5. Incompatible materials

	Strong oxidising agents.
--	--------------------------

10.6. Hazardous decomposition products

Holdtite A649

Revision 0

Revision date 2017-09-12

10.6. Hazardous decomposition products

Burning produces irritating, toxic and obnoxious fumes.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

Acetone	Dermal Rat LD50: 5500mg/kg	Oral Rat LD50: 3000mg/kg
---------	----------------------------	--------------------------

SECTION 12: Ecological information

12.1. Toxicity

Acetone	Bluegill sunfish LC50/96h: 8300mg/l
---------	-------------------------------------

12.3. Bioaccumulative potential

Partition coefficient

Holdtite A649 =-0.24 log P

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1090

14.2. UN proper shipping name

ACETONE

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	II
---------------	----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

Holdtite A649

Revision 0

Revision date 2017-09-12

IMDG	
EmS Code	F-E S-D

IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

	<p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
--	---

SECTION 16: Other information**Other information**

Text of risk phrases in Section 3	<p>R10 - Flammable R11 - Highly flammable. R22 - Harmful if swallowed. R36 - Irritating to eyes. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.</p>
Text of Hazard Statements in Section 3	<p>EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</p>

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---