

THREAD SEALANT WITH PTFE PART NO. 49494

DESCRIPTION

Dynatex® Thread Sealant with PTFE is a non-toxic, non-drying thread sealing compound consisting of a blend of non-melting grease, PTFE particles and other inert solid fillers engineered to produce a leak-proof seal. **Dynatex® Thread Sealant with PTFE** does not contain lead, graphite, molybdenum disulfide, or clay fillers.



TYPICAL SPECIFICATIONS

TEST	ASTM METHOD	RESULT
Color	----	White
Usable Temperature Range (Brushable from +15°F)	----	-35°F to 550°F+
Specific Gravity	----	1.2
N.L.G.I. Grade	----	1
Penetration	D-217	310-340
Flash Point, °F	D-92	400
100 hr., 5% Salt Spray	B-117	No Rust

USAGE

Dynatex® Thread Sealant with PTFE can be used to seal all thread joints in plastic, aluminum, monel, or stainless steel lines against water, natural gas, LPG, gasoline and other services. It is also effective on connections, pipe bungs, bolts, flange seals, and as a gasket-parting compound.

NOTE: This product is not recommended for pure oxygen systems

ADVANTAGES

- ◆ Contains PTFE
- ◆ Non-Hardening
- ◆ Prevents Corrosion
- ◆ Non-Toxic
- ◆ Positive Seal
- ◆ Holds Pressure to 10,000 PSI

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The user's exclusive remedy and the supplier's sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® A division of Accumetric, LLC

350 Ring Road Elizabethtown, Kentucky 42701 USA (800) 999-2937 TEL (270) 769-5557 FAX (270) 769-6418
Outside U.S. TEL +1(270) 769-5557 FAX +1(270) 769-6418
Email: sales@dynatexinc.com Website: www.dynatexinc.com