

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

Holdtite S54

Revision 0
Revision date 2015-12-02

SECTION 1: Identification	of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Holdtite S54
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC1] Adhesives, sealants;
1.3. Details of the supplier of	the safety data sheet
Company	Bondchem
Address	Unit 10 Lawson Street
	Dock Road Industrial Estate
	North Shields
	Tyne and Wear
Wal	NE29 6TF
Web	www.bondchem.com
Telephone	+44 (0)191 2586990
Fax	+44 (0)191 2596853
1.4. Emergency telephone nu	
Emergency telephone number	+44(0)191 2586990
Company	Bondchem (Head Office)
	24 hours (Diverted out of office hours)
SECTION 2: Hazards ident	ification
2.1. Classification of the subs	stance or mixture
2.1.1. Classification -	Xi; R36/37/38-43
1999/45/EC	Symbols: Xi: Irritant.
Main hazards	Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;
2.2. Label elements	
Hazard pictograms	<u>•</u>
Hazard pictograms Signal Word	Warning
	Warning Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Signal Word	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation.
Signal Word Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Revision 0
Revision date 2015-12-02

2.2. Label elements

2.2. Laber elements	
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .
Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
	P321 - Specific treatment (see on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement:	P501 - Dispose of contents/container to
Disposal	
2.3. Other hazards	
Other hazards	This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. Classification M-fac (%w/w)	ctor.
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19	1 - 10% O; R7 T; R23 Xn; R21/22-48/20/22 C; R34 N; R51/53	
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21	30 - 40% Xi; R43	
2-Hydroxyethyl methacrylate	607-124-00-X	868-77-9	212-782-2	01-2119490169-29	20 - 30% Xi; R36/38 R43	
Cumene	601-024-00-X	98-82-8	202-704-5		0 - 0.5% R10 Xn; R65 Xi; R37 N; R51/53	
1-Acetyl-2-Phenylhydrazine		114-83-0			1 - 10% T; R25 Xi; R36/37/38-43	
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)		128-37-0		01-2119555270-46	0 - 0.5% R53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19	1 - 10%	GOrg. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314; Aquatic Chronic 2: H411;	
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21	30 - 40%	Skin Sens. 1: H317;	
2-Hydroxyethyl methacrylate	607-124-00-X	868-77-9	212-782-2	01-2119490169-29	20 - 30%	6 Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317;	
1-Acetyl-2-Phenylhydrazine		114-83-0			1 - 10%	6 Acute Tox. 3: H301; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; STOT SE 3: H335;	

SECTION 4: First aid measures

4.1. Description of first aid measures

· · · · · · · · · · · · · · · · · · ·	
Inhalation	Move the exposed person to fresh air. Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if irritation or symptoms persist.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Keep the affected person warm and at rest. Rinse mouth thoroughly. Drink 1 to 2 glasses of water. Seek medical attention.



Revision 0 Revision date 2015-12-02

	Revision date 2015-12-02
4.2. Most important symptom	s and effects, both acute and delayed
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin. Eczema. Itching.
Ingestion	Ingestion may cause nausea and vomiting.
4.3. Indication of any immedia	ate medical attention and special treatment needed
	Remove the affected person from the source of contamination immediately. If you feel unwell, seek medical advice (show the label where possible).
SECTION 5: Firefighting me	easures
5.1. Extinguishing media	
	Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical.
5.2. Special hazards arising fr	om the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	In case of fire and/or explosion do not breathe fumes. Wear:. Protective equipment. Self-
	contained breathing apparatus. Cool fire exposed containers with waterspray.
SECTION 6: Accidental rele	ease measures
6.1. Personal precautions, pro	otective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
6.2. Environmental precaution	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for	containment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Do not allow runoff water to enter sewers or drains. Do not empty into drains; dispose of this material and its container in a safe way.
6.4. Reference to other section	
	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind, keeping bystanders also upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak side up to prevent escape of liquid.
SECTION 7: Handling and	storage
7.1. Precautions for safe hand	lling
7.2. Conditions for safe storage	Avoid contact with eyes and skin. Wear suitable protective clothing and gloves. Wear eye/face protection. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing. Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly
	labelled containers.
7.3. Specific end use(s)	
	Industrial uses: Uses of substances as such or in preparations at industrial sites.
Suitable packaging	
	LDPE Plastic containers.
SECTION 8: Exposure cont	trols/personal protection
8.1. Control parameters	




Revision 0 Revision date 2015-12-02

8.1.1. Exposure Limit Values

Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10
(_,, , _ , _ , _ , _ , _ , _ , _ , _	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Cumene	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 125
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 250
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Coloui	Brown
Odoui	Characteristic
рН	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Relative density	> 1.12 (H2O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	= 1500 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available



Revision 0
Revision date 2015-12-02

9.2. Other information

Conductivity No data available
Surface tensior No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Avoid contact with:. Copper and its alloys. Peroxides. Strong acids.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

If product is contaminated and becomes unstable the product may polymerize and produce an exothermic reaction.

10.4. Conditions to avoid

Heat. Keep only in the original container at a temperature not exceeding 15 °C.

10.5. Incompatible materials

Acids. Copper and its alloys. Strong oxidising agents.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and obnoxious fumes.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

1-Acetyl-2-Phenylhydrazine	Oral Mouse LD50: 270mg/kg	
2-Hydroxyethyl methacrylate	Dermal Rat LD50: >5000mg/kg	Oral Rat LD50: >5000mg/kg
Butylated Hydroxytoluene	Oral Rat LD50: 1700mg/kg	Oral Mouse LD50: 800-1600mg/kg
	Dermal Guinea Pig LD50: >8000mg/kg	
Cumene	Dermal Rat LD50: 12.3mg/kg	Oral Rat LD50: 2910mg/kg
Cumene hydroperoxide	Inhalation Rat LC50/4 h: 220ppm	Oral Rat LD50: 382mg/kg
Triethyleneglycol Dimethacrylate	Oral Mouse LD50: >200mg/kg body	
	weight	

SECTION 12: Ecological information

12.1. Toxicity

2-Hydroxyethyl methacrylate	Algae IC50/72h: 836.0000 mg/l	Fish LC50/96h: 100.0000 mg/l
Butylated Hydroxytoluene	Daphnia EC50/48h: 1.4400 mg/l	
Cumene	Fish LC50/96h: 6.3200 mg/l	
Cumene hydroperoxide	Fish LC50/96h: 3.9000 mg/l	
Triethyleneglycol Dimethacrylate	Fish LC50/96h: 16.4 mg/l	

12.3. Bioaccumulative potential

Partition coefficient

AS26 No data available

12.5. Results of PBT and vPvB assessment

The product does not contain any substances classified as PBT or vPvB.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

Disposal methods

Copyright © 2015 ChemSoft Limited. All rights reserved.



Revision 0
Revision date 2015-12-02

Disposal methods		
	For disposal within the EC, the appropriate code according to the European Waste	
	Catalogue (EWC) should be used.	
Disposal of packaging		
	Empty containers can be sent for disposal or recycling.	
SECTION 14: Transport inf	ormation	
14.1. UN number		
	The product is not classified as dangerous for carriage.	
14.2. UN proper shipping nam	ne	
	The product is not classified as dangerous for carriage.	
14.3. Transport hazard class(es)	
	The product is not classified as dangerous for carriage.	
14.4. Packing group		
	The product is not classified as dangerous for carriage.	
14.5. Environmental hazards		
	The product is not classified as dangerous for carriage.	
14.6. Special precautions for	user	
	The product is not classified as dangerous for carriage.	
14.7. Transport in bulk accord	ling to Annex II of MARPOL 73/78 and the IBC Code	
	The product is not classified as dangerous for carriage.	
SECTION 15: Regulatory in	formation	

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

SECTION 16: Other information

Other information

Text	of risk	phrases	in S	ection
3				

R7 - May cause fire.

R10 - Flammable

R21/22 - Harmful in contact with skin and if swallowed.

R23 - Toxic by inhalation.

R25 - Toxic if swallowed.

R34 - Causes burns.

R36/37/38 - Irritating to eyes, respiratory system and skin.

R36/38 - Irritating to eyes and skin.

R37 - Irritating to respiratory system.

R43 - May cause sensitisation by skin contact.

R48/20/22 - Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic



Revision 0 Revision date 2015-12-02

Other information		
	environment.	
	R53 - May cause long-term adverse effects in the aquatic environment.	
	R65 - Harmful: may cause lung damage if swallowed.	
Text of Hazard Statements in	n Skin Sens. 1: H317 - May cause an allergic skin reaction.	
Section 3	Skin Irrit. 2: H315 - Causes skin irritation.	
	Eye Irrit. 2: H319 - Causes serious eye irritation.	
	Acute Tox. 3: H301 - Toxic if swallowed.	
	STOT SE 3: H335 - May cause respiratory irritation.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use,	
	storage and handling of the product. This information is correct to the best of our knowledge and	
	belief at the date of publication however no guarantee is made to its accuracy. This information	
	relates only to the specific material designated and may not be valid for such material used in	
	combination with any other materials or in any other process.	

