

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

Holdtite T75

Revision 0 Revision date 2015-06-16

CHOMICAL TARREST	Revision date 2010-0			
	of the substance/mixture and of the company/undertaking			
1.1. Product identifier				
Product name	T75			
1.2. Relevant identified uses	of the substance or mixture and uses advised against			
Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC1] Adhesives, sealants;			
1.3. Details of the supplier of	the safety data sheet			
Company	Bondchem			
Address	Unit 10 Lawson Street			
	Dock Road Industrial Estate			
	North Shields			
	Tyne and Wear			
	NE29 6TF			
Web	www.bondchem.com			
Telephone	+44 (0)191 2586990			
Fax	+44 (0)191 2596853			
1.4. Emergency telephone nu	mber			
Emergency telephone numbe	mergency telephone number +44(0)191 2586990			
Company	Bondchem (Head Office)			
	24 hours (Diverted out of office hours)			
SECTION 2: Hazards iden	tification			
2.1. Classification of the subs				
2.1.1. Classification -	Xi; R36/38-43			
1999/45/EC	Symbols: Xi: Irritant.			
Main hazards	Irritating to eyes and skin. May cause sensitisation by skin contact.			
2.1.2. Classification - EC	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319;			
1272/2008	Calair 21210			
2.2. Label elements				
Hazard pictograms				
Signal Word	Warning			
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation.			
	Skin Sens. 1: H317 - May cause an allergic skin reaction.			
	E Iit 2. II210. Common aminus and imitation			

P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Eye Irrit. 2: H319 - Causes serious eye irritation.

P264 - Wash thoroughly after handling.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statement:

Prevention

2.2. Label elements

Precautionary Statement:

Response

P302+P352 - IF ON SKIN: Wash with plenty of water/.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Other hazards This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19	0.5 - 1%	O; R7 T; R23 Xn; R21/22-48/20/22 C; R34 N; R51/53	
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21	30 - 40%	Xi; R43	
2-Hydroxyethyl methacrylate	607-124-00-X	868-77-9	212-782-2	01-2119490169-29	20 - 30%	Xi; R36/38 R43	
Cumene	601-024-00-X	98-82-8	202-704-5		0 - 0.5%	R10 Xn; R65 Xi; R37 N; R51/53	
p-Toluenesulfonyl hydrazide		1576-35-8	216-407-3		0 - 0.5%	T; R25 R44	
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)		128-37-0		01-2119555270-46	0 - 0.5%	R53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19	0.5 - 1%	Org. Perox. EF: H242; Acute	
						Tox. 3: H331; Acute Tox. 4:	
						H312; Acute Tox. 4: H302;	
						STOT RE 2: H373; Skin Corr	•
						1B: H314; Aquatic Chronic 2	:
						H411;	
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21	30 - 40%	Skin Sens. 1: H317;	
2-Hydroxyethyl methacrylate	607-124-00-X	868-77-9	212-782-2	01-2119490169-29	20 - 30%	Eye Irrit. 2: H319; Skin Irrit. 2	:
						H315; Skin Sens. 1: H317;	
p-Toluenesulfonyl hydrazide		1576-35-8	216-407-3		0 - 0.5%	Flam. Liq. 3: H226; Flam. Sol	
						2: H228; Self-react. CD:	
						H242; Acute Tox. 3: H301;	
Butylated Hydroxytoluene		128-37-0		01-2119555270-46	0 - 0.5%	Aquatic Chronic 1: H410;	
(2,6-Di-tert-butyl-p-cresol)							

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if irritation or symptoms persist.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Keep the affected person warm and at rest. Rinse mouth thoroughly. Drink 1 to 2 glasses of water. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.



40.34 1	Revision date 2015-00-10
<u> </u>	and effects, both acute and delayed
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin. Eczema. Itching.
Ingestion	Ingestion may cause nausea and vomiting.
4.3. Indication of any immedia	nte medical attention and special treatment needed
	Remove the affected person from the source of contamination immediately. If you feel unwell, seel medical advice (show the label where possible).
SECTION 5: Firefighting m	easures
5.1. Extinguishing media	
	Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical.
5.2. Special hazards arising fro	·
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	In case of fire and/or explosion do not breathe fumes. Wear:. Protective equipment. Self-contained breathing apparatus. Cool fire exposed containers with waterspray.
SECTION 6: Accidental rele	ease measures
6.1. Personal precautions, prot	ective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
6.2. Environmental precaution	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for	
6.5. Wethous and material for	
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Do not allow runoff water to enter sewers or drains. Do not empty into drains; dispose of this material and its container in a safe way.
6.4. Reference to other section	s
	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind, keeping bystanders also upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak side up to prevent escape of liquid.
SECTION 7: Handling and	storage
7.1. Precautions for safe handl	<u> </u>
	Avoid contact with eyes and skin. Wear suitable protective clothing and gloves. Wear eye/face protection. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing. Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
7.2. Conditions for safe storage	e, including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
7.3. Specific end use(s)	
	Industrial uses: Uses of substances as such or in preparations at industrial sites.
Suitable packaging	1 1
1 0 0	LDPE Plastic containers.
SECTION 8: Exposure conti	rols/personal protection
8.1. Control parameters	
8.1.1. Exposure Limit Values	



8.1.1. Exposure Limit Values

Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)	WEL8-hrlimitppm: -	WEL8-hrlimitmg/m3: 10
, and the same	WEL15minlimitppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Cumene	WEL8-hrlimitppm: 25	WEL8-hrlimitmg/m3: 125
	WEL15 min limit ppm: 50	WEL 15 min limit mg/m3: 250
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls





8.2.1. Appropriate engineering controls

8.2.2. Individual protection

measures

Eye / face protection

Skin protection -

Handprotection

Respiratory protection

8.2.3. Environmental exposure controls

Occupational exposure controls

Ensure adequate ventilation of the working area.

Wear chemical protective clothing.

Approved safety goggles

Chemical resistant gloves (PVC).

In case of insufficient ventilation, wear suitable respiratory equipment.

Not normally required.

Wash hands at the end of each shift and before eating, smoking and using the toilet. Wash skin promptly if skin becomes contaminated. Promptly remove any clothing that has become contaminated.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Red
Odour	Characteristic
рН	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Relative density	> 1.12 (H2O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	> 6000 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available



9.2. Other information

Conductivity	No data available	
Surface tension	No data available	
SECTION 10: Stability and reactivity		

10.1. Reactivity

Avoid contact with:. Copper and its alloys. Peroxides. Strong acids.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

If product is contaminated and becomes unstable the product may polymerize and produce an exothermic reaction.

10.4. Conditions to avoid

Heat. Keep only in the original container at a temperature not exceeding 15 °C.

10.5. Incompatible materials

Acids. Copper and its alloys. Strong oxidising agents.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and obnoxious fumes.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

2-Hydroxyethyl methacrylate	Dermal Rat LD50: >5000mg/kg	Oral Rat LD50: >5000mg/kg
Butylated Hydroxytoluene	Oral Rat LD50: 1700mg/kg	Oral Mouse LD50: 800-1600mg/kg
	Dermal Guinea Pig LD50: >8000mg/kg	
Cumene	Dermal Rat LD50: 12.3mg/kg	Oral Rat LD50: 2910mg/kg
Cumene hydroperoxide	Inhalation Rat LC50/4 h: 220ppm	Oral Rat LD50: 382mg/kg
p-Toluenesulfonyl hydrazide	Oral Rat LD50: 283mg/kg	Dermal Rabbit LD50:>2000mg/kg
Triethyleneglycol Dimethacrylate	Oral Mouse LD50: >200mg/kg body weight	

SECTION 12: Ecological information

12.1. Toxicity

2-Hydroxyethyl methacrylate	Algae IC50/72h: 836.0000 mg/l	Fish LC50/96h: 100.0000 mg/l
Butylated Hydroxytoluene	Daphnia EC50/48h: 1.4400 mg/l	
Cumene	Fish LC50/96h: 6.3200 mg/l	
Cumene hydroperoxide	Fish LC50/96h: 3.9000 mg/l	
Triethyleneglycol Dimethacrylate	Fish LC50/96h: 16.4 mg/l	

12.3. Bioaccumulative potential

Partition coefficient

AT07 No data available	
11107 140 data available	

12.5. Results of PBT and vPvB assessment

The product does not contain any substances classified as PBT or vPvB.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

Disposal methods

Disposal methods					
	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.				
Disposal of packaging					
	Empty containers can be sent for disposal or recycling.				
SECTION 14: Transport info	ormation				
14.1. UN number					
	The product is not classified as dangerous for carriage.				
14.2. UN proper shipping nam	e				
	The product is not classified as dangerous for carriage.				
14.3. Transport hazard class(es	14.3. Transport hazard class(es)				
	The product is not classified as dangerous for carriage.				
14.4. Packing group					
	The product is not classified as dangerous for carriage.				
14.5. Environmental hazards					
	The product is not classified as dangerous for carriage.				
14.6. Special precautions for user					
	The product is not classified as dangerous for carriage.				
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code					
	The product is not classified as dangerous for carriage.				
SECTION 15: Regulatory information					

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

SECTION 16: Other information

Other information

Text	of	ris	k p	hras	es i	n Sec	tion
3							

R7 - May cause fire.

R10 - Flammable

R21/22-Harmful in contact with skin and if swallowed.

R23 - Toxic by inhalation.

R25 - Toxic if swallowed.

R34 - Causes burns.

R36/38 - Irritating to eyes and skin.

R37 - Irritating to respiratory system.

R43 - May cause sensitisation by skin contact.

R44 - Risk of explosion if heated under confinement.

R48/20/22 - Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic



Other information					
	environment. R53 - May cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed.				
Text of Hazard Statements in	Skin Sens. 1: H317 - May cause an allergic skin reaction.				
Section 3	Skin Irrit. 2: H315 - Causes skin irritation.				
	Eye Irrit. 2: H319 - Causes serious eye irritation.				
	Flam. Liq. 3: H226 - Flammable liquid and vapour.				
	Flam. Sol. 2: H228 - Flammable solid.				
	Self-react. CD: H242 - Heating may cause a fire.				
	Acute Tox. 3: H301 - Toxic if swallowed.				
	Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.				
Further information					
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.				